



## 2D FLUORESCENT GLOBES

- Wattage: 16W & 28W
- 2 pin comes with integral starter
- 2 pin only suitable for use with conventional control gear
- 4 pin does not have integral starter
- 4 pin is suitable for use with high frequency electronic control gear
- Eight times the life of incandescent
- 2 pin: GR8 base
- 4 pin: GR10q base
- Not suitable for dimming



8,000  
HRS

1 YEAR  
WARRANTY

CODE	DESCRIPTION	TECHNICAL DATA				DIMENSIONS		
		BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	LENGTH (mm)	WIDTH (mm)	CARTON QTY
<b>2D16WGR10QWW</b>	2D FL 16W GR10Q 4 PIN 3100K	GR10Q	3100	1050	16	141	138	1/20
<b>2D16WGR10QL</b>	2D FL 16W GR10Q 4 PIN 6400K	GR10Q	6400	1050	16	141	138	1/20
<b>2D16WGR8WW</b>	2D FL 16W GR8 2 PIN 3100K	GR8	3100	1050	16	141	138	1/20
<b>2D16WGR8DL</b>	2D FL 16W GR8 2 PIN 6400K	GR8	6400	900	16	141	138	1/20
<b>2D28WGR10QWW</b>	2D FL 28W GR10Q 4 PIN 3100K	GR10Q	3100	1800	28	207	205	1/20
<b>2D28WGR10QL</b>	2D FL 28W GR10Q 4 PIN 6400K	GR10Q	6400	1930	28	207	205	1/20
<b>2D28WGR8WW</b>	2D FL 28W GR8 2 PIN 3100K	GR8	3100	1930	28	207	205	1/20
<b>2D28WGR8DL</b>	2D FL 28W GR8 2 PIN 6400K	GR8	6400	1930	28	207	205	1/20

Brochure updated on 09.12.2016