

HIBTRI

LED Power Switchable TRI-CCT High Bay

IP65


**5 YEAR
REPLACEMENT
WARRANTY**

Product Features:

- Input voltage range: 120-277V AC 50Hz
- Constant current LED driver inbuilt
- Housing & Faceplate: powder coated Aluminium
- Heatsink: Aluminium
- Diffuser: Clear PC
- LED chips: 2835 LED
- Power factor: ≥ 0.95
- Flex & plug: 1.2m
- Ambient temp: -20 to 50°C
- Not suitable for dimming
- Suitable for 2-way switching
- Suitable for use with motion & microwave sensors



HIBTRI1



**TRI-POWER
TRI-CCT
ALL IN ONE**

45,000hr Lifetime	90° Beam Angle	IP65 Rated	5YEAR Replacement Warranty
----------------------	-------------------	----------------------	---

PART NO.			HIBTRI1
LUMENS	100W	3000K	15500LM
		4000K	17000LM
		5700K	15500LM
	150W	3000K	21000LM
		4000K	22500LM
		5700K	21000LM
	200W	3000K	27000LM
		4000K	29500LM
		5700K	28000LM
POWER FACTOR			≥ 0.95
DIMENSIONS			Ø320 X H121.1mm
BOX WEIGHT			2.8kg
BOX DIMENSIONS			360x360x160cm
CARTON QTY			1/1

