



DIMMABLE SURFACE SERIES

LED Surface Mounted Ceiling Lights IP65



Product Features

- Input voltage: 240V AC 50/60Hz
- Wattage: 13W
- Material: aluminium
- Epistar COB LED chip
- Power factor: 0.9
- Ambient temp: -20 to 40°C
- Suitable for dimming
- Recommended Universal Trailing Edge and Leading Edge dimmers
- Not suitable for 2-way switching
- 3 year replacement warranty



Recommended dimmers: (2-8 pcs /dimmer)

- | | |
|-----------------------|----------------------|
| (1) CLA LYNX | (2) CLA-VELA |
| (3) Clipsal 32ELEDM | (4) Clipsal 31E2PUDM |
| (5) Clipsal 32E450UDM | (6) Clipsal 32E450LM |
| (7) HPM CAT250L | (8) HPM CAT250T |
| (9) HPM CAT400T | |

Technical data

| CODE | DESCRIPTION | KELVIN (K) | LUMENS (LM) | WATT (W) | CRI | BEAM ANGLE | IP | DIMM | DIAM (mm) | DEPTH (mm) | CARTON QTY |
|------------------|---|------------|-------------|----------|-----|------------|------|------|-----------|------------|------------|
| SURFACE13 | 13W GLOSS WH LED S/M CEILING LIGHT 3000K | 3000 | 800 | 13 | >80 | 40° | IP65 | YES | Ø105 | 146 | 1/12 |
| SURFACE14 | 13W GLOSS WH LED S/M CEILING LIGHT 5000K | 5000 | 900 | 13 | >80 | 40° | IP65 | YES | Ø105 | 146 | 1/12 |
| SURFACE15 | 13W GLOSS BLK LED S/M CEILING LIGHT 3000K | 3000 | 800 | 13 | >80 | 40° | IP65 | YES | Ø105 | 146 | 1/12 |
| SURFACE16 | 13W GLOSS BLK LED S/M CEILING LIGHT 5000K | 5000 | 900 | 13 | >80 | 40° | IP65 | YES | Ø105 | 146 | 1/12 |

UPDATED ON 17.02.2017