

## Features

- Five-Colour
- Low profile
- Edge-lit
- Opal diffuser
- 2x2-way terminals for easy loop in loop out installation

## Applications



Residential, Hallways, Stairwells,  
Porches, Wall & Ceilings, Bathrooms

## Warranty

5 years



2x2-way terminals  
for easy loop in  
loop out installation



## Product Data

Order Code	Wattage	CCT	Lumen Output	Beam Angle	Size (ØxH)mm	Weight (kg)
181007V	13W	3K / 4K / 5K / 5.7K / 6.5K	1300Lm	120°	Ø244x23	0.42
181007VBK	13W	3K / 4K / 5K / 5.7K / 6.5K	1300Lm	120°	Ø244x23	0.42
181005V	20W	3K / 4K / 5K / 5.7K / 6.5K	2000Lm	120°	Ø294x23	0.71
181005VBK	20W	3K / 4K / 5K / 5.7K / 6.5K	2000Lm	120°	Ø294x23	0.71
181006V	24W	3K / 4K / 5K / 5.7K / 6.5K	2400Lm	120°	Ø424x23	1.30
181006VBK	24W	3K / 4K / 5K / 5.7K / 6.5K	2400Lm	120°	Ø424x23	1.30

[1] Operating temperature: -20°C~+40°C

[2] Voltage: 220-240V

[3] PF: 0.9

[4] Inrush current I<sub>peak</sub> 0.5 (A), Inrush current T<sub>width</sub> 0.98 (µs)

[5] Earth leakage current <0.7mA

