

## G4 Bi Pin PLV Series

- 12V AC/DC
- Silica Gel Lamps
- G4 Socket Base
- 80+ CRI
- 25,000 Hour rated
- UV Infused Inhibitors
- LEDs are measured and tested @ 12 Volts
  - Longest Life occurs at 12 Volts
- Stainless Steel Pins
- Silver Soldering for Long Lasting Performance
- Made for use in Enclosed Fixtures and Damp Location
- 2700K and 3000K Colour Temperature
- Constant Current Driver for Long Life
- Dimmable with Lutron Magnetic Dimmers
  - Dimming may Reduce Life Span
- PLV1-G4
  - 120 Lumens, 1.5 Watts, .13 VA, .7 PF
- PLV2-G4
  - 160 Lumens, 2.5 Watts, .17 VA, .7 PF
- PLV2-G4
  - 230 Lumens, 3.5 Watts, .21 VA, .7 PF



G4 1.5W



G4 2.5W



G4 3.5W

PART NUMBER	Watts	COLOUR TEMP	LUMENS	INPUT
PLV1-G4-27K	1.5W	2700K	120	12V AC/DC
PLV1-G4-30K	1.5W	3000K	120	12V AC/DC
PLV2-G4-27K	2.5W	2700K	160	12V AC/DC
PLV2-G4-30K	2.5W	3000K	160	12V AC/DC
PLV3-G4-27K	3.5W	2700K	230	12V AC/DC
PLV3-G4-30K	3.5W	3000K	230	12V AC/DC