

PANEL-606 Panel Light



Description

45W LED Panel light. Natural anodised aluminium frame, opal diffuser. These are ideal as ceiling light for T-Bar ceilings, or by using a plaster recessed frame, ideal for commercial applications such as office spaces. Fully dimmable with Domus dimmer series.




Specification Features

Input Voltage:	240VAC
Power (W):	45W
IP rating (IP):	44
Lumens (lm):	Warm White 3000K - 2950lm
	Neutral White 4000K - 3000lm
	White 6000K - 3050lm
LED type:	High efficiency SMD LED
CCT:	3000K - 4000K - 6000K
CRI:	≥80
Dimmable:	Yes*
Mounting Type:	Recessed into standard grid ceiling or via optional plaster trim kit for plaster board ceilings or via optional wire suspended or surface mounted kit.
Lifespan (hrs):	50,000hrs
Dimensions:	(L) 595mm x (W) 595mm x (H) 10mm
* Dimmable when used in conjunction with the Domus dimmer series	

* Dimmable when used in conjunction with the Domus dimmer series. May work with others but not tested.

Diagrams / Additional



Product Code:	PANEL-606-SLR-WW
Order Code:	19314
Colour:	Warm White LED 3000K
Product Code:	PANEL-606-SLR-NW
Order Code:	19313
Colour:	Neutral White LED 4000K
0010011	PANEL-606-SLR-W
0010011	
Product Code:	PANEL-606-SLR-W



LED Panel Trim (Recessed Plaster Frame) Order Code: 19327 Product Code: TRIM606-W



Order Code:19331Product Code:SM-KIT606-AColour:Aluminium AnodisedProduct Code:SM-KIT606-WOrder Code:19335

Satin White

Colour:

Domus 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com Specification subject to change without prior notice.