

# MAJESTIC COOLAH CEILING FAN



Satin Brass with Beech Blades

**Installation Locations:**

Indoor

**Recommended Height:**

There should be at least 2.1m between the lowest point of the fan blades and the floor.

**Top of canopy cover to lowest point of the fan:**

Approximately 350mm

**Motor:**

16 Pole, 153mm x 18mm motor  
Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

**Motor Housing:**

Materials: Pressed Steel

**Available Colours :**

White, White Birch, Brushed Chrome, Antique Brass & Satin Brass

**Blades:**

Sizes: 1320mm (52")  
Materials: NZ Plywood (Flat colours– Painted & Lacquered, Wood grain colours - Laminated & Lacquered)  
Blade Pitch: 12°

**Available Blade Colours:**

White (Rattan Insert) White Birch, Matt Black, Beech, Walnut (Rattan Insert) & Brushed Silver

**Extra Information:**

Introduced into the HPI range in 2002  
3 Speed Pull cord  
Light Adaptable  
Reversible  
Wall control does not come standard

**Standard Canopy Cover:**

Suitable for flat and pitched ceilings up to 28°

**Wall Controller Speed Capacitor Values:**

3µF & 2µF

**Rotational Diameter:**

1320mm (52") Blade Sweep

**Weight Including Packaging:**

Complete fan 1320mm (52"): 6.6kg

**Packaging Dimensions (cm):**

Complete fan 1320mm (52"): 50L x 30W x 22H

**Accessories:**

Remote Control  
Extension Down Rod 21mm diameter  
45° Ceiling Kit (for pitched ceilings)  
T-Hook for ceiling roses  
Universal Mounting Brace

**Warranty**

2 years "in home" covering major defects  
3 Years additional covering motor only (not labour)  
Remotes -1 year "in home" covering major defects.  
(receiver and handpiece)  
Lights -1 year "in home" covering major defects

**Airflow and Efficiency:**

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised For USA Energy Star compliance.

	HIGH	MED	LOW
<b>RPMS</b>	195	132	95
<b>WATTS</b>	67	29.2	16.8
<b>AIRFLOW<sup>^</sup>: AUS-ES / USA-ES</b>	8518 / 11499	5793 / 7821	4264 / 5756
<b>EFFICIENCY<sup>^</sup>: AUS-ES / USA-ES</b>	127.13 / 171.63	198.39 / 267.84	253.81 / 342.62


<sup>^</sup> Airflow measured in Cubic metres/ Hour (CM/HR), Efficiency measured in CM/HR per watt (CMH/W)

# For full warranty details please see Hunter Pacific International's website [www.hunterpacific.com.au](http://www.hunterpacific.com.au)

# MAJESTIC RANGE CEILING FAN LIGHTING



## 78mm Halogen Light (MAX 100W)




- Cost effective
- Colour—warm white
- Dimmable
- Compact in size



78mm linear Halogen Light globe

## E27 Light ( MAX 2x40W)



- Accepts a variety of lamps, e.g. incandescent, fluorescent.
- Cost effective
- Compatible with some CFL lamps



E27

### GLACIER STYLE GLASS





### ECLIPSE STYLE GLASS



#### Colours Available:

All light kits are available in most motor colours ~ White, White Birch, Black, Brushed Chrome, Polished Brass, Antique Brass, Burnt Copper and Stainless Steel.

## GX53M 14W Compact Fluorescent Light



- A Base
- B Lamp Assembly
- C Tube

- Low wattage
- High light output
- Liquid mercury free
- Colour—Warm white/Cool white colour temperatures available
- Low heat
- 12000 hour life span
- 2700k or 3000k


#### Packaging Dimensions

17H x 25W x 25L

#### Weight

1.5 kg

## Flat 6, 26W Fluorescent Lamp



- High Efficiency (EEL=A2)
- High light output
- Liquid mercury free
- Low heat
- Fewer shadows visible
- Dimmable on certain fan models; ecO<sup>2</sup> & Ice Range (with Model 089 FLDR)
- 4100k

^ All light kits must be installed by a licensed electrician. For further information about correct installation procedures, please see [www.hunterpacific.com.au](http://www.hunterpacific.com.au)

# For full warranty details please see Hunter Pacific International's website [www.hunterpacific.com.au](http://www.hunterpacific.com.au)