



UFO SHB26SE - 80W

Dimmable 1-10V, IP65 LED highbay

Application

Versatile, low wattage LED highbay, ideal for low ceiling commercial applications.

Design Specifications

- Integral high performance 1-10V dimmable control gear with flex and plug
- CCT 5000K, CRI >80
- Robust, low profile black die-cast aluminium body profile. IP65/IK08 protection
- High efficiency LED optics, with an impressive 180lm/W performance
- 90° beam distribution, polycarbonate lens
- Optional plug and play corridorSTANDBY sensor









Performance

- Dimmable - **YES**
- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	Beam Angle (°)	CCT (K)
	SHB26SE80NDL	240	80	14400	90	5000
	SHB25HES/RC					
	SHB23MP/CS					
	LM-DALI010B					
	SHB26PMR150					
	SHB26PPR150					

CRI	Body Colour	Diameter (mm)	Dim (mm)	Mass (kg)	IPART
80	BLACK	320	137(H)	2.2	YES
	REMOTE CONTROL				N/A
	CORRIDOR SENSOR				
	DALI SIGNAL CONVERTER				
	SILVER	500	236(H)		
CLEAR PC	480	250(H)			

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

THE NEW ESS106 IS SMALL IN SIZE BUT BIG ON FEATURES.



For more
information
please
scan me

